Application No.: 10/811,936

Reply to Election of Species Requirement

dated September 25, 2006

to Office Action of August 23, 2006

Page 2 of 6

AMENDED CLAIM SET

Docket No.: 0649-1082PUS1

The claims have been amended as set forth in the following listing of the claims:

1. (original) A safety device of a vehicle having a curtain air bag stowed along

a roof side rail of the vehicle, comprising:

a seat belt anchor attached to said roof side rail for anchoring a seatbelt, said seatbelt

anchor having a protruded part protruding towards an interior of the vehicle such that the

protruding part overpasses the curtain air bag.

2. (original) The safety device of claim 1, further comprising:

a mounting part adapted to support the curtain air bag on the roof side rail,

wherein the mounting part and the seat belt anchor are attached to the roof side rail as a

unit.

3. (original) The safety device of claim 1, wherein said seat belt anchor has a

first end thereof mounted on the roof side rail, and a second end thereof supporting the seat belt,

and the protruding part is provided between the first end and the second end.

4. (original) The safety device of claim 3, wherein the second end is positioned

adjacent to a side window glass of the vehicle when the seat belt anchor is attached to the roof

side rail.

5. (original) The safety device of claim 1, wherein said seat belt anchor moves

towards the interior of the vehicle.

Application No.: 10/811,936

Reply to Election of Species Requirement

dated September 25, 2006

to Office Action of August 23, 2006

Page 3 of 6

6. (original) A safety device of a vehicle having a curtain air bag stowed along

a roof side rail of the vehicle, comprising:

a mounting bracket adapted to be attached to the roof side rail and for supporting a

Docket No.: 0649-1082PUS1

seatbelt anchor such that the mounting bracket underpasses the curtain air bag between the roof

side rail and the curtain air bag, the mounting bracket having a rising member that allows

deployment of the curtain air bag away from an obstacle provided in a deploying direction of the

curtain air bag.

7. (original) The safety device of claim 6, further comprising:

a mounting part adapted to support the curtain air bag on the roof side rail,

wherein the mounting part and the mounting bracket are attached to the roof side rail as a

unit.

8. (original) A safety device of claim 6, wherein the curtain air bag is located

above the rising member.

9. (currently amended) The safety device of elaim 1 claim 7, wherein the mounting

part and the seat belt anchor are attached to the roof side rail by a common fastening member.

10. (original) The safety device of claim 7, wherein the mounting part and the

mounting bracket are attached to the roof side rail by a common fastening member.

11. (currently amended) The safety device of claim 6, wherein the mounting part

mounting bracket has a first end thereof provided with an insertion portion inserted into a

Application No.: 10/811,936 Docket No.: 0649-1082PUS1

Reply to Election of Species Requirement

dated September 25, 2006

to Office Action of August 23, 2006

Page 4 of 6

fastening hole provided in the roof side rail and a second end thereof fixed to the roof side rail,

and the rising member is formed between the first end and the second end.

12. (original) The safety device of claim 11, wherein the mounting bracket has a

seatbelt anchor mounting part provided between the rising member and the second end for

supporting the seatbelt anchor.

13. (original) The safety device of claim 11, further comprising:

a mounting part adapted to support the curtain air bag on the roof side rail,

wherein the mounting bracket has an air bag mounting part provided between the first

end and the rising member, and the mounting part is placed at the air bag mounting part and

attached to the roof side rail with the mounting bracket by a common fastening member.